

TimeCutter® 4225, Model No. 75742TA



TECHNICAL SPECIFICATIONS AND FEATURES

Engine	Toro LC2P77F, Spec 139-0600 (original), 139-0601 (service), 16.8 kW (22.5 hp), 708 cc, overhead valve, V-twin (cast iron sleeves) single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. High idle speed set at 3,300 +/-100 rpm. Standard style paper / foam air cleaner fitted, Optional Canister style available as an accessory.
Construction	Riveted and bolted 10 gauge steel.
Deck Size	106.7 cm (42.0 inch).
Deck Configuration	Right side discharge, two blade mid-mounted rotary. Drawn 13 gauge (2.28 mm) formed steel housing with welded mounting brackets. Frame supported. Left and right front mounted anti-scalp rollers.
Deck Spindles	Die cast aluminum spindle housing (2). Permanently lubricated sealed precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
Height of Cut	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
Hydro Drive Unit	Dual Hydro-gear ZT-2100 hydrostatic transaxles, belt drive with self-tensioning system.
Ground Speed	Mow: 0 to 11.3 km/h (0 to 7.0 mph). Trim: 0 to 8.9 km/h (0 to 5.5 mph). Tow: 0 to 6.4 km/h (0 to 4.0 mph). Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
Wheel Base	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
Steering Control	Ergonomic, adjustable steering levers with heavy-duty dampeners.
Width	Deflector Down: 136.0 cm (53.6 inches). Deflector Up: 116.8 cm (46.0 inches).
Overall Length	190.5 cm (75.0 inches)
Overall Height	97.0 cm (38.2 inches).
Tyres	Front - 11 x 4.0-5.0, 2 ply, smooth tread, pneumatic. Rear - 18 x 7.5-8, 4 ply, turf tread, pneumatic.
Fuel Tank Capacity	11.4 litres (single tank).
Net Weight	240.0 kg (529.0 lbs.).
Seat	40.67 cm (16.0 inch) handcrafted contoured seat, adjustable, hinged mounting, with spring suspension.
Warranty	Consumer: Machine 3 years, Engine & Transaxles 3 years, Wear Parts 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). Commercial: Machine & Transaxles 30 days, Engine 3 year/300 hours (whichever occurs first), Wear Parts 90 days, Battery: 30 days. Attachments: 1 year. NOTE: Engine warranty is through Toro Australia. <i>For all other conditions, refer to the online The Toro Warranty statement.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB02-20, issued August 28, 2020.

Issue Date: 28 August, 2020

PLEASE NOTE: The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

ACCESSORIES AND ATTACHMENTS

Product	Part No.
Twin Bagger Kit - 42 inch Stamped Deck	79410
Blowout Ring Kit	137-7048
Recycler Kit – 42 inch	137-7042
Hourmeter Kit	116-5461
Heavy Duty Air Cleaner Kit***	135-6195
ROPS Kit	79485
Slope Sensor Kit, TimeCutter	79486
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056
Deck Foot Lift Assist Kit	140-2059

Jack requires mount kit 140-2711 and cannot be used if Step Kit and Assist Handle is fitted.

Product	Part No.
Floor Mat Kit	140-2060
Seat Armrest Kit	140-2058
Seat Cover (W/O armrests)	117-0096
Assist Bar Kit	140-2052
Storage Cover	490-7516
Striping Kit – 42 inch	137-5030 or 140-5198
Front Weight Kit	140-2050
Deluxe Seat Kit	140-2057
Engine Maintenance Kit – Standard Air Cleaner	139-0646
Engine Maintenance Kit – Heavy Duty Air Cleaner	139-0649

*** Highly recommended if machine is fitted with a bagger attachment.

REGULAR MAINTANENCE ITEMS

Product	Part No.
Air Cleaner Element Complete	136-7806
Air Cleaner Foam Element	136-7804
H/Duty Air Cleaner Element	108-3811
Engine Oil Filter	136-7848
Engine Fuel Filter	133-1563
Engine Valve Cover Gasket (2 required)	127-9295
Spark Plug	Champion RN9YC or NGK BPR6ES

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SF, SG, SH, SJ or SL. Engine Oil SAE-30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 2.3 litres With oil filter change – 2.4 litres
Transaxle Oil	SAE 20W-50 API Engine Oil
Transaxle Oil Capacity	1.6 to 1.65 litres per side

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	137-7046
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	117-7468	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	140-2736
Deck Spindle Drive Belt	119-8819	Rear Tyre	140-2729
Deck Spindle Pulley	139-2433	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-2403
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Belt Cover	108-7889		

Blades

Blade Type	Part No.	Blade Type	Part No.
Standard and Bagger Application (Hi-Lift)	137-1999-03	Optional (Recycler / Mulch)	117-5376-03