

TimeCutter[®] MX 5075, Model No. 75755TA



TECHNICAL SPECIFICATIONS AND FEATURES

Engine	Toro LC2P77F, Spec 139-0602 (original), 139-0603 (service), 18.3 kW (24.5 hp), 708 cc, overhead valve, V-twin (cast iron sleeves) single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. High idle speed set at 3,300 +/- 100 rpm.
Construction	Riveted and bolted 10-gauge steel.
Deck Size	127.0 cm (50.0 inch).
Deck Configuration	Right side discharge, three blade mid-mounted rotary. Fabricated 10-gauge steel housing with welded reinforcements, mounting brackets, and gauge wheel brackets. Frame supported. Left, centre and right front mounted anti-scalp rollers with four height positions.
Deck Spindles	Die cast aluminum spindle housing (3). Permanently lubricated precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
Height of Cut	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
Hydro Drive Unit	Dual Hydro-gear ZT-2200 hydrostatic transaxles, belt drive with self-tensioning system.
Ground Speed	Mow: 0 to 11.3 km/h (0 to 7.0 mph).
	Trim: 0 to 8.9 km/h (0 to 5.5 mph).
	Tow: 0 to 6.4 km/h (0 to 4.0 mph).
	Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
Wheel Base	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
Steering Control	Ergonomic, adjustable steering levers with dampeners.
Width	Deflector Down: 156.2 cm (61.5 inches).
	Deflector Up: 129.5 cm (51.0 inches).
Overall Length	190.0 cm (75.0 inches) – rear bumper to front edge of caster wheel.
Overall Height	
Tyres	Front - 11 /600-5, 4 ply rated, smooth tread, pneumatic.
	Rear - 18 x 9.5-8, 4 ply rated, turf tread, pneumatic.
Fuel Tank Capacity	11.4 litres (single tank).
Net Weight	287.6 kg (634.0 lbs.).
Seat	45.7 cm (18 inch) handcrafted high back contoured seat with large bolsters and thick cushion. Standard with pivotable armrests. Seat pan is fastened to MyRIDE suspension platform.
Warranty	Consumer: Machine 3 years, Engine & Transaxles 3 years, Wear Parts 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only).
	Commercial: Machine & Transaxles 30 days, Engine 3 year/300 hours (whichever occurs first), Wear Parts 90 days, Battery: 30 days.
	Attachments: 1 year.
	For all other conditions, refer to the online The Toro Warranty statement.

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB02-20, issued August 28, 2020.

PLEASE NOTE: The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

ACCESSORIES AND ATTACHMENTS

Product	Part No.
Twin Bagger Kit	79412
Bagging Enhancement Kit	139-7459
Hour meter Kit	116-5461
Recycler Kit	139-3240
Deck Maintenance Jack#	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056
ROPS Kit	79485
MyRIDE Heavy Duty Spring Kit	140-2051
Seat Cover (with armrests)	117-0097
Storage Cover	490-7516

Product	Part No.
Striping Kit	121-5706, or 140-5160
Heavy Duty Air Cleaner Kit***	135-6195
Assist Bar	140-2052
Sunshade Kit	140-2054
Floormat Kit	140-2061
Slope Sensor Kit	79486
Toro Standard V-Twin Maintenance Kit	139-0646
Toro H/Duty V-Twin Maintenance Kit	139-0649

Jack requires mount kit 140-2711.

*** Highly recommended if machine is fitted with a bagger attachment.

REGULAR MAINTANENCE ITEMS

Product	Part No.	Product	Type / Capacity	
Air Cleaner Element Complete	136-7806	Engine Oil Type	Detergent engine oil, API service	
Air Cleaner Foam Element	136-7804		SF, SG, SH, SJ or SL. Engine Oil SAE-30 for normal	
H/Duty Air Cleaner Element	108-3811		conditions – otherwise refer to	
Engine Oil Filter	136-7848		Operator's Manual.	
Engine Fuel Filter	133-1563	Engine Oil	Without oil filter change – 2.3 litres	
Spark Plugs	Champion [®] RN9YC	Capacity	With oil filter change – 2.4 litres	
	or NGK [®] BPR6ES	Transaxle Oil	SAE 20W-50 API Engine Oil	
Engine Valve Cover Gasket	127-9295 (2 required)	Transaxle Oil Capacity	1.6 to 1.65 litres per side	

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	138-7502
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	127-3408	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	138-7553
Deck Spindle Drive Belt	119-8820	Rear Tyre	140-2731
Deck Spindle Pulley	139-7454	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-2403
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Drive Belt Cover	139-3293		

Blades

Blade Type	Part No.	Blade Type	Part No.
Standard and Bagger Application (Hi-Lift)	115-5059-03	Optional (Recycler / Mulch)	115-5062-03