

Z Master® G3 Commercial 6000, Model No. 72960



TECHNICAL SPECIFICATIONS AND FEATURES

	CATIONS AND FEATURES	
Engine	Kawasaki FX921V-ES04-R, 23.1 kW (31.0 hp), 999 cc, Carbureted V-twin.	
Deck Size	152.4 cm (60.0 inches).	
Deck Configuration	Right side discharge, three blade mid-mount rotary. Fabricated 7-gauge steel (80-Grade top plate) Turbo Force deck with welded reinforcements, mounting brackets, and gauge wheel brackets. The deck has four adjustable gauge wheels, and is suspended from the frame by four chains. The deck has a 'no tools' adjustable discharge baffle.	
Deck Spindles	2.54 cm (1.0 inch) diameter splined spindle shaft turning in non-greaseable ball bearings. 22.86 cm (9.0 inch) diameter aluminum spindle housing.	
Height of Cut	2.5 cm to 14.0 cm (1.0 to 5.5 inches) with 6.4 mm (0.25 inch) increments. Foot operated lift assist.	
Hydro Drive Unit	Twin Parker unitized 16 cc pump and 280.2 cc wheel motor assemblies. 1.6 litre integrated reservoir, spin on filter, cooling fans, internal shock valves and heavy duty components.	
Ground Speed	18.5 km/h – forward max.	
Steering Control	Ergonomic, adjustable steering levers with heavy duty dampeners.	
Width	134.6 cm (53.0 inches) – Outside of rear tyres.	
Overall Width	192.3 cm (75.7 inches) – With the deflector down. 156.7 cm (61.7 inches) – With the deflector up (gate width).	
Overall Length	211.1 cm (83.1 inches) – ROPS down.	
Overall Height	179.1 cm (70.5 inches) – ROPS up.	
Tyres	Front – 13 x 6.5 inch - 6, smooth tread, semi-pneumatic. Rear – 24 x 12.0 inch - 12 Turf Master.	
Fuel Tank Capacity	45.4 litres.	
Net Weight	575.6 kg (1269.0 lbs.).	
Folding ROPS	Standard.	
Seat	Deluxe handcrafted triple tone Bullhorn suspension folding seat with large bolsters and thick cushion. This seat is rubber mounted giving 3-D motion isolation. The seat is hinged to can pivot forward to allow for access underneath the seat.	
Armrests	Standard, pivotable.	
Warranty	Machine: 5 year / 1400 hour (no hour limit in the first 2 years). Engine: 3 years. Wear Parts (belts, blades, tyres etc.): 90 days. Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). Attachments: 1 year. NOTE: Engine warranty is through Kawasaki USA, but administered by Toro Australia. For all other conditions, refer to The Toro Warranty statement accompanying the machine.	

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

For additional technical and servicing information regarding this mower refer to Service Bulletin G3SB01/20, issued 24 March, 2020.

Re-Issue Date: 29 April, 2021

ACCESSORIES AND ATTACHMENTS

Product	Part No.
Hitch Kit	109-9487
Jack Mounting Kit	127-6665
Jack Kit#	127-6666
Z-Stand Kit	121-4811
Light Kit (ROPS Mounted)	116-1154
Work Light Kit (Frame Mounted)	135-7320
Bimini Folding Sunshade	115-4510
Operator Discharge Chute Kit	117-3600
Roller Striper Kit	115-7470
Power Deck Lift Kit	132-5986
Filter Minder	99-4664
Bucket Holder	137-9216
Bucket – 5 Gallon	133-2533
Trimmer Mount Kit	137-9769

Product	Part No.
Toro Rider Arm Rest Bag	490-7320
Seat Cover	117-0095
Recycler Kit	139-6655
E-Z Vac Blower and Drive Kit	78553
E-Z Vac Triple Soft Bagger*	78563
E-Z Vac DFS Bagger*	78567
Leaf Bagging Enhancement Kit	137-9769
Toro Rider Over Seat Bag	490-7317
Trash Bag Holder Kit	TC26
Spark Arrestor Screen	75-6880
Toro Deluxe Rider Cover	490-7319
Front Weight Kit	140-4958
24x12N12 Tweel Turf Wheel	139-7891

Jack kit requires mounting kit 127-6665.

REGULAR MAINTANENCE ITEMS

Product	Part No.
Air Cleaner Primary Element	119-5944
Air Cleaner Safety (Inner) Element	119-5945
Engine Oil Filter	49065-7010 or KW10761
Engine Fuel Filter	121-4570 or 135-2743
Spark Plugs	NGK BPR5ES
Transmission Oil Filter (2 required)	117-0390

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SF, SG, SH, SJ, SL or higher. SAE 20W-50 or SAE 30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 1.7 litres With oil filter change – 1.9 litres
Transmission Oil	Toro Pro-Series HYPR-OIL 500 hydraulic oil.
Transmission Oil Capacity	Approximately 1.6 litres each side with filter change. Final check via dipstick.

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	126-9835	Deck Spindle Drive Belt Flanged Pulley	132-4734
Traction Drive Assembly Idler Pulley	109-8076	Deck Drive Belt Idler Arm Flat Pulley	132-9425
Traction Drive Assembly Engine Pulley	109-9905	Deck Anti-Scalp Roller	1-603299
PTO Clutch Kit	126-4185	Blade Attaching Screw	109-9220
Deck Spindle Drive Belt	132-5982	Blade Attaching Hex Bushing	137-9787
Deck Spindle Housing (with bearings)	137-9780	Deck Discharge Rubber Deflector	108-5029
Deck Spindle Bearing (2 required)	116-0720	Fuel Tank Cap	126-1789
Deck Spindle Shaft	138-6045	Front Castor Wheel & Axle Assembly	127-9528
Deck Spindle Pulley	138-6059	Rear Tyre	1-633993
Deck Spindle Pulley Attaching Nut	116-7306	Ignition Key	63-8360
Deck Spindle Pulley Washer	103-2802	Battery	104-8162
Deck Spindle Bottom Guard	137-9784	Throttle Control Cable Assembly	133-1816
Deck Spindle Top Bearing Guard	103-1330	Choke Cable	133-1873
Deck Spindle Drive Belt Flat Pulley	136-5404		

Blade Types

60 in Blade Types	Single Blade Part No.	Six Pack Blade Part No.
High Flow (Standard)	140-1240	140-4877
Low Flow (Sand and Leaves)	140-4854	140-4879
Medium Flow (Bahai)	140-4853	140-4878
Atomic	140-1241	140-4880
Recycler	140-4855	140-4881

^{*} For use with 78553.